



REVISIONS [http://loel.ucolick.org/manual/ADC/schematics/ADC\\_power\\_sh\\_2.sch.pdf](http://loel.ucolick.org/manual/ADC/schematics/ADC_power_sh_2.sch.pdf)

04-20-04	RENUMBERED ALL CONNECTORS
04-23-04	REMOVED CONNECTORS J405 AND J406 AND ADDED J403 CONNECTION FROM PIN C TO PIN D
04-26-04	ADDED NOTE FOR PRIMARY LIMIT +5V
06-14-04	CORRECTED LABELS AT CONNECTOR J301
06-17-04	CORRECTED PIN NUMBERS OF J405 AND J405. ADDED CONNECTOR J402 LABEL TO 24V INPUT
10-14-04	ADDED EMERGENCY STOP SWITCH
11-24-04	ADDED 4TH ANALOG INPUT FROM TEMPERATURE SENSOR BOARD (AN4) FOR UPDATED BOARD WITH +24V POWER SUPPLY MONITORING
02-22-07	REWired MOTOR CABLE SO THAT THE CABLE HAS TWO 20 AWG WIRES IN PARALLEL TO REDUCE VOLTAGE DROP TO MOTOR - G. TOLLETH
04-26-07	ADDED 36V SERVO SUPPLY TO INCREASE MOTOR SPEED

UNIVERSITY OF CALIFORNIA LICK OBSERVATORY		ADC STAGE KECK ADC	
DES'N BY: B. Alcott	ORIGIN DATE: 09-16-03	DWG. NO. EL-3610	NUM. 2 OF 6
Last SN	MODIFY DATE: 04-26-07	REV. A	
PRINT TIME: 08:38:02	PRINT DATE: Tue May 01, 2007		
PATH: ADC\		ADC_stage.sch	