

8000 Series

Liquid Flow Meter



Advanced microprocessor-based flow measurement technology in a compact, leak-tight package.



- » Flow ranges from 0.02 to 60 GPM / 0.1 to 227 LPM
- » Accuracy of 3% of flow range
- » Liquid temperatures from -40 to 90°C can be monitored at up to 30°C ambient temperature without remote-mounting the electronics!
- » Enhanced accuracy and stability from digital signal processing
- » 15 alarm values selectable in 5% steps – plus AutoAlarm™!
- » Standard 0–5 VDC or 0–10 VDC, and 4–20 mA outputs
- » Specialized calibration to account for viscosity effects of fluid and operating temperature
- » Bright tricolor LED provides clear visual indication of flow status
- » NEMA 4X / IP65 packaging ensures reliable performance in wet environments

Proteus 8000 Series instruments provide accurate, rugged, reliable and cost-effective measurement of heat transfer fluids and other liquids from -40 to 90°C. Customized versions can be adapted for use with liquid temperatures to 150°C and above. A built-in relay can be used to sound an alarm or shut down a system before damage is done to valuable equipment and products.

AT A GLANCE

Flow Ranges	0.02 to 60 GPM 0.1 to 227 LPM
Temperature Limit ¹	90°C / 194°F
Pressure Limit ²	100 PSI / 689 kPa
Output Formats	0–5 VDC or 0–10 VDC 4–20 mA
RoHS Compliant	Yes
CE Marked	Yes
NEMA 4X / IP65 Enclosure	Standard


¹ 150°C / 302°F and above with customized versions.

² 250 PSI / 1723 kPa with optional metal faceplate.

How It Works

As liquid flows through the sensor body, it causes the rotor to spin. Magnets embedded in the rotor switch a Hall-Effect sensor mounted in the sensor body. The rotational frequency of the rotor is measured by a microcomputer, and scaling factors entered into flash memory allow the volumetric flow rate to be calculated. Flow rate information is output as 0–5 or 0–10 VDC and 4–20 mA.


A built-in relay is programmed to change state when the measured flow rate falls below a pre-selected alarm value. A bright LED relay status indicator is GREEN when the measured rate of flow is greater than $1.1 \times$ the selected alarm flow rate, AMBER when within 10% of the alarm flow rate and RED if below the alarm flow rate.



Easy Trip Point Adjustment

A 16-position switch provides simple and accurate selection of the alarm flow rate. The switch is housed under a screw closure with a leak-tight O-ring seal to prevent unintentional adjustment.

Selecting switch positions 1 to F sets the trip point flow rate in 5% steps from 10% to 80% of the maximum flow rate of the instrument. The unique AutoAlarm™ function allows the operator to set the trip point value based on a selected measured reference flow. To set the AutoAlarm, simply move the switch to the zero position after adjusting the reference flow; the LED status indicator blinks for five seconds and the alarm is set!



POSITION	% OF MAXIMUM FLOW RATE
0	AutoAlarm™ » Sets trip point based on reference flow rate
1	10%
2	15%
3	20%
4	25%
5	30%
6	35%
7	40%
8	45%
9	50%
A	55%
B	60%
C	65%
D	70%
E	75%
F	80%

Wide Temperature Range and Accurate Flow Calibration

Standard brass and stainless steel models are capable of monitoring fluids at temperatures from -40 to 90°C. Customization is available to extend the liquid temperature limit to above 150°C. Proteus' world-class calibration capability allows us to deliver instruments with temperature- and fluid-specific calibrations to help you control your most critical processes.

Contact our flow experts at sales@proteusind.com or (650) 964-4163 for assistance in identifying the optimum solution for your most demanding applications!

Flow Visibility

A clear polysulfone faceplate allows the rotor to be fully visible, telling you at a glance if your cooling fluid is flowing.

Optional metal faceplates enable brass and stainless steel flow meters to be operated at pressures up to 250 PSI / 1723 kPa.



Flow Ranges, Connections and Materials

FLOW RANGE*		CONNECTION	MODEL NUMBER		
GPM	LPM		POLYPROPYLENE	BRASS	STAINLESS STEEL
0.02 – 0.13	0.1 – 0.5	1/4" FNPT	08004PN013	08004BN013	08004SN013
0.05 – 0.3	0.2 – 1.1	1/4" FNPT		08004BN03	08004SN03
0.06 – 0.6	0.2 – 2.2	1/4" FNPT	08004PN06	08004BN06	08004SN06
0.1 – 1.4	0.4 – 5.3	1/4" FNPT	08004PN1	08004BN1	08004SN1
0.2 – 2.5	0.8 – 9.5	1/4" FNPT	08004PN2	08004BN2	08004SN2
0.2 – 2.5	0.8 – 9.5	9/16-18 SAE			08006SA2
0.3 – 4.5	1.1 – 17	1/4" FNPT	08004PN4	08004BN4	08004SN4
0.3 – 4.5	1.1 – 17	9/16-18 SAE			08006SA4
0.6 – 9.0	2.2 – 34	3/8" FNPT		08006BN9	08006SN9
0.6 – 10	2.2 – 38	3/8" FNPT	08006PN10		
0.8 – 10	3.0 – 38	3/4-16 SAE			08008SA10
1.0 – 14	3.8 – 53	1/2" FNPT	08008PN14	08008BN14	08008SN14
1.2 – 16	4.5 – 60	3/4" FNPT		08012BN16	08012SN16
1.2 – 16	4.5 – 60	1 1/16-12 SAE			08012SA16
1.5 – 19	5.7 – 72	3/4" FNPT	08012PN19		
3.0 – 40	11 – 151	3/4" FNPT		08012BN40	08012SN40
4.0 – 40	15 – 151	1" FNPT		08016BN40	08016SN40
4.0 – 40	15 – 151	1 5/16-12 SAE			08016SA40
4.0 – 50	15 – 189	1" FNPT	08016PN50		
5.0 – 60	19 – 227	1" FNPT		08016BN60	08016SN60

*Listed flow ranges are for water at 25°C / 77°F.

MATCHING AN 8000 SERIES FLOW METER TO YOUR APPLICATION

- Select a flow body material that is chemically compatible with your fluid.
- Check the operational temperature and pressure limits to identify suitable materials.
- Select your flow meter with a range so that
 - your nominal flow rate is around 50–60% of the upper flow limit of the instrument, and
 - your maximum flow rate is less than the upper flow limit of the instrument.
- For specialized heat-transfer fluids such as Galden® or Fluorinert™, or if using positionable elbows, select SAE straight-thread connections.

For assistance in selecting the 8000 Series flow meter that is best suited to your flow control task, contact Proteus Technical Support at tech@proteusind.com or (650) 964-4163.

Temperature and Pressure Operating Limits

FLOW SENSOR MATERIAL	FACEPLATE MATERIAL	TEMPERATURE LIMIT*		PRESSURE LIMIT	
		°C	°F	PSI	kPa
Polypropylene	Clear Polysulfone	70	158	75	517
Brass	Clear Polysulfone	90	194	100	689
	Brass	90	194	250	1723
Stainless Steel	Clear Polysulfone	90	194	100	689
	Stainless Steel	90	194	250	1723

*This is the fluid temperature that can be sustained with the flow meter cooled by ambient air up to 30°C / 86°F.

Other Wetted Materials

COMPONENT	AVAILABLE MATERIALS	
	STANDARD	OPTIONAL
Rotor	Kynar®	PPS
O-Ring	Viton®	Buna-N, Silicone Rubber
Rotor Shaft	316 Stainless Steel	Alumina, Sapphire

Performance Characteristics

The flow measurement capability of 8000 Series instruments can be qualified by three characteristics:

ACCURACY	<p>The closeness of an indicated value to the actual value</p> <p>Accuracy is expressed as a $\pm\%$ of the highest value at which the calibration adjustment is made.</p>
LINEARITY	<p>The closeness of a calibration to curve to its best-fit straight line</p> <p>Linearity is expressed as the maximum measured deviation of any calibration point from the ideal response line during a single calibration cycle.</p>
REPEATABILITY	<p>The ability of the instrument to reproduce readings when the same measured value is presented to it consecutively, under the same conditions and in the same direction</p> <p>Repeatability is expressed as the maximum difference between output readings.</p>

» How They Are Reported

The measurement capability of each 8000 Series instrument is stated on a Certificate of Conformance delivered with each unit.

A Calibration Certificate stating improved accuracy of $\pm 1\%$ of reading for a single flow point is available at additional cost. This calibration adjustment is referenced to a flow standard whose response is controlled to $\pm 0.5\%$ of the selected flow point. Standard calibrations are made with water at room ambient temperature.

» Calibration and Measurement Uncertainty










Accuracy specifications for 8000 Series instruments include the uncertainty of the calibration process. Uncertainty statements for flow calibrations are available upon request.

Accuracy - Standard	$\pm 3\%$ of flow range with standard validation
Accuracy - Validated	$\pm 2\%$ of calibration value
Linearity	$\pm 1.5\%$ of flow range from 0.1 to 1.0 \times flow range
Repeatability	$\pm 1\%$ of flow range from 0.1 to 1.0 \times flow range
Output Range	0–5 VDC OR 0–10 VDC and 4–20 mA
Hysteresis	5% of flow range
Pressure Drop	< 10 PSI at maximum flow rate for all versions except 08004BN06, 08004SN06 and 08004PN08. Contact Proteus Sales for more information.

Electrical Requirements

Input Power Voltage	+24 VDC $\pm 10\%$
Input Power Consumption	< 1 W
Relay Contacts Maximum Current	1 A at 48 VDC
Voltage Output Maximum Sourcing Current	15 mA at 2 VDC output
Current Loop Voltage Compliance	0–22 VDC at 24 VDC input voltage

Wiring

WIRE COLOR	FUNCTION	WIRE COLOR	FUNCTION
 (BARE)	Shield	 YELLOW	Relay Common
 RED	+24 VDC	 BLUE	Relay Normally Open
 BLACK	Ground	 WHITE	Relay Normally Closed
 BROWN	Voltage Output	 GREEN	Analog Ground
 ORANGE	Current Output		


Compliance and Certifications

8000 Series instruments are compliant with the standards and directives listed below. Complete details, including information on suitability and restrictions, are available in the 8000 Series Technical Reference Manual.

- » **RoHS Compliance** Restriction of Hazardous Substances (RoHS) Directive 2002/95/EC
- » **CE Marking** Electromagnetic Capability (EMC) Directive 89/336/EEC
- » **FCC Compliance** FCC Part 15 for protection against radio frequency interference

Dimensions and Drawings

The size of an 8000 Series instrument is dependent on its flow range, and ranges from (HWD) 2.74"×3.00"×1.82" to 3.16"×3.60"×2.68" (69.60×76.20×46.10mm to 80.26×91.44×68.7mm). Outline and 3D drawings are accessible on the Proteus Industries website at www.proteusind.com/8000. Solid models are available upon request; please contact Proteus Technical Support.



Need More Information?

- » **Download the 8000 Series Technical Reference Manual**

This comprehensive document, containing technical descriptions, performance specifications, flow response and pressure drop curves, installation and mounting instructions, maintenance guidelines and other valuable information is accessible at www.proteusind.com/8000.


- » **Contact Proteus Technical Support**


A flow measurement expert will be pleased to answer your questions! Contact tech@proteusind.com or (650) 964-4163.

Proteus: Customization Experts

Bring us your specifications and let us create a flow management solution to meet your exact requirements. Materials can be modified or improved for compatibility with your fluid; flow ranges can be matched to large connections; adaptations can be implemented for high and low temperatures; and multiple devices can be integrated in cost-effective manifold assemblies for liquid distribution, measurement and control.

Fittings will be properly positioned, the entire unit will be certified to be leak tight, and all electrical connections will have been tested end-to-end. Our lean manufacturing processes and ISO 9001 certified procedures ensure that your devices will arrive on time, every time, and ready for use.



 **Proteus Industries Inc.**
 340 Pioneer Way, Mountain View, CA 94041
 Tel: (650) 964-4163 Fax: (650) 965-0304
www.proteusind.com sales@proteusind.com

Information in this document was correct at the time of printing; however, specifications are subject to change as Proteus Industries' continuous improvement processes establish new capabilities.

© Proteus Industries Inc. All rights reserved. All other company and product names may be trademarks of their respective companies.

8000DS Rev 001 03/2009